

CALTANE™ SOLVENTS

TYPICAL PROPERTIES

TEST NAME	METHOD	124A	78A	96 GS	96I	96H	98H	120A
API Gravity @ 60 °F	ASTM D4052	66.2	64.2	64.5	66.3	64.8	64.9	60.6
Specific Gravity @ 60/60 °F	ASTM D1250	0.7157	0.7230	0.7217	0.7154	0.7208	0.7205	0.7366
Density @ 60 °F (Pounds Per Gallon)	ASTM D1250	5.967	6.028	6.018	5.964	6.010	6.007	6.141
Distillation, IBP (°F)	ASTM D86	95	116	116	152	174	204	223
Distillation, 5% (°F)	ASTM D86	140	175	181	178	189	206	229
Distillation, 10% (°F)	ASTM D86	160	193	193	184	191	207	231
Distillation, 20% (°F)	ASTM D86	191	208	204	188	194	208	233
Distillation, 30% (°F)	ASTM D86	223	213	210	194	197	208	235
Distillation, 40% (°F)	ASTM D86	237	220	213	200	201	209	238
Distillation, 50% (°F)	ASTM D86	243	223	215	206	205	210	241
Distillation, 60% (°F)	ASTM D86	249	225	217	212	210	211	246
Distillation, 70% (°F)	ASTM D86	256	229	219	216	214	212	252
Distillation, 80% (°F)	ASTM D86	265	235	222	220	219	214	261
Distillation, 90% (°F)	ASTM D86	278	249	231	225	225	218	275
Distillation, 95% (°F)	ASTM D86	288	269	231	231	230	223	285
Distillation, Dry Point (°F)	ASTM D86	290	278	240	236	235	234	290
Vapor Pressure @ 20 °C (mm Hg)	ASTM D2879	44	69	60	71	84	60	26
Kauri-Butanol Value	ASTM D1133	28.7	32.1	34.3	34.0	35.1	33.8	34.7

TECHNICAL ASSISTANCE

For product or technical questions, contact your Sales Representative or Calumet Product Support at (800) 437-3188 or email technical@calumet.com.

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Typical values only represent the values one would expect if the property were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values are not based on a statistically relevant number of tests.

The information in this document relates only to the named product. The user is solely responsible for all determination regarding any use and any process.

Download a digital copy of this brochure.

